

Advanced TOYOTA technology introduces 2.0 and 2.5 ton series towing tractors.

Designed to meet demanding professional needs, the fast traveling speed and small turning radius bring outstanding maneuverability to any worksite.

Complete Potential

Powerful 2Z Diesel Engine (42-2TD20.25 models)



Toyota offers its powerful 3.5 liter 2Z diesel engine on 42-2TD20,25 models. It makes heavy work fast and effortless.

Rated Power

kW /2,200rpm

Rated Torque

216 N-m /1,600rpm

Piston Displacement

3,469 cc

Travel Speed

 $30\,{}^{\text{km/h}}_{\text{(No Load)}}\,23\,{}^{\text{km/h}}_{\text{(with 16t Load)}}$


Small Turning Radius

Small turning radius offers comfortable maneuvering even in narrow space.

Turning Radius (Outside)
[(02-)2TG20,25] (02-)2TD20,25]
3-050 mm

[42-2TD20,25]

3,200_{mm}



Complete Operability

Operator's Compartment

Steering wheel with power steering system and adjustable steering column provide excellent maneuverability.

Meters and gauge in an integrated layout makes it easy to check the vehicle status.



Drawbar Lever & Pin

The operator has a clear view of the drawbar pin from the seat,and can easily operate the drawbar lever. A hydraulic drawbar lever is available as an option.







Seat

This seat supports to reduce fatigue during long hours operation.
A suspension seat is optionally available to help soften the ride even more.



NEW Retractable Seat Belt OPT

The seat belt with ELR (Emergency Locking Retractor) is available. ELR allows the belt to freely extend and retract with operator movement, yet locks the belt during a sudden stop or upon impact.



Low and Non-slip Floor

The low and non-slip floor supports frequent getting on and off.



Automatic Transmission

(02-, 42- Model)

The automatic transmission automatically shifts from L to 2 to D, it provides smooth operation.



Steel Cabin OPT

The steel cabin helps to boost both comfort and safety even in extremely cold or rainy climate.







Engine Powered Towing Tractor

2.0 and 2.5 ton Series

Main Specifications


Model		2TG20 2TD20	2TG25 2TD25	
Engine Model		4Y 1DZ-Ⅱ ,(2Z)	4Y 1DZ-Ⅱ ,(2Z)	
Maximum Drawbar Pull	kg N	2,000 19,500	2,500 24,500	
Gradeability*	% (tan θ)	46	46	
Overall Width A	mm	1,445	1,445	
Turning Radius (Outside) B	mm	3,050 (3,200)	3,050 (3,200)	
Overall Height C	mm	1,390	1,390	
Overall Length D	mm	3,020 (3,130)	3,020 (3,130)	





Engine Specifications

Model		TOYOTA 4Y	TOYOTA 1DZ-II	TOYOTA 2Z
		Gasoline	Diesel	Diesel
Piston Displacement	cc	2,237	2,486	3,469
Rated Power/r.p.m	kW	39.7/2,400	40.5/2,400	48.5/2,200
	JIS ps	54/2,400	55/2,400	66/2,200
Rated Torque/r.p.m	N-m	162/1,800	167/1,600	216/1,600
	JIS kg-m	16.5/1,800	17/1,600	22/1,600



Other Models

Main Specifications

Model		3TG35 3TD35	40-3TD35	3TD45
Engine Model		2F 2H	2D	2D
Maximum Drawbar Pull	kg N	3,500 34,300	3,500 34,300	4,500 44,100
Gradeability*	% (tan θ)	46	46	46
Overall Width A	mm	1,900	1,900	1,900
Turning Radius (Outside) B	mm	4,500	4,500	4,500
Overall Height C	mm	1,730	1,730	1,730
Overall Length D	mm	3,835	3,835	3,835

Engine Specifications

Model		TOYOTA 2F Gasoline	TOYOTA 2H Diesel	TOYOTA 2D Diesel
Piston Displacement	cc	4,230	3,980	6,494
Rated Power/r.p.m	kW	49/2,100	51/2,200	66/2,100(77/2,100)
	JIS ps	67/2,100	70/2,200	90/2,100(105/2,100)
Rated Torque/r.p.m	N-m	255/1,200	235/1,600	323/1,400(392/1,600)
	JIS kg-m	26/1,200	24/1,600	33/1,400(40/1,600)

NOTE:() for Powershift





All rights reserved by Toyota Industries Corporation.



The data in this leaflet is determined based on our standard testing condition.
The performance may vary depending on the actual specification and condition of the vehicle as well as the condition of the operating area.
Availability and specifications depend on market and are subject to change without notice.
Due to photography and printing, color of actual vehicle may vary from this leaflet. Some photos have been computer-enhanced.
Please consult your Toyota representative for details.
Photographs may include optional equipment.